


2 POLI - MONOFASE
SENZA SPAZZOLE - CONDENSATORE

- > Autoregolati
- > IP 23
- > Tensione standard: 230 V - 50 Hz
- > Precisione di tensione: $\pm 8\%$
- > Corrente di cortocircuito superiore a 3 In
- > Accoppiamenti: IM B35

2 POLES - SINGLE PHASE
BRUSHLESS - CAPACITOR

- > Self-regulated
- > IP 23
- > Standard voltage: 230 V - 50 Hz
- > Voltage accuracy: $\pm 8\%$
- > Short circuit current greater than 3 In
- > Couplings: IM B35

model	power		η 4/4		mass	dimensions		
	kVA	%	kVA	%		Kg (approx)	A	B
	50 Hz - 3000 r.p.m.		60 Hz - 3600 r.p.m.			mm	mm	mm
R80 MBL	1,2	68	1,5	69	9	221	60	143
R80 LBL	2,2	73	2,7	75	13,8	261	100	183

IM B35 - J609a (c19) - B3/B9 (c23)

cone	d	a	b	α
19	18,5	54,7	24	$2^{1/4}$ x foot
23	23,0	8,0	30	1:5

Cono 19 fornito come standard
 Cone 19 supplied as standard

